

# GPSC SERIES

X-arm projector lift



# GPSC SERIES MOTORIZED PROJECTOR LIFT

X-arm projector lift is an ultra-thin electric frame that is designed for small and medium-sized projectors with a small installation space. It is widely used in conference rooms, training rooms, and multimedia classrooms. The lift mechanism uses X-type compound robotic arm to activate its movement, natural stable operation, precise electronic stroke positioning, one-touch setting, simplified operation; hidden installation design, can be integrated with ceiling.

GPSC-5010 X-arm projector electric lift offers an open-top design, suitable for installation of small height and small height of concrete. GPSC-5006 only requires a ceiling height of 135mm.



Closed Position



GPSC-5010B X-arm projector electric lift embraces a sealed box-type design. When closed, the X-arm crane and projector can be concealed within the box. The decorative cover and the box are magnet-controlled to facilitate the installation or disassembly of the equipment.



The decorative cover and the box are magnetized for easy disassembly.



## Product Features



Wireless Remote Control




Hinged joint gears



Dual Motor Intelligent Drive System



Detachable projector mount



Projector mounting bracket level adjustment



Built-in wire storage buckle

## Specification

Model	Size (mm) W x D x H	Ceiling Opening Size (mm)	Decorative Cover Size (mm)	Maximum Lift Distance (mm)	Control Method	Product Weight (mm)	Projector Maximum Size (mm)	Voltage (V)	Power (W)
GPSC5006	580x580x150	590x590	600x600	600	DC5-12V trigger control / dry contact / remote	17	480x480x135	~220/50Hz	50
GPSC5010	580x580x215	590x590	600x600	1000	DC5-12V trigger control / dry contact / remote	20	480x480x160	~220/50Hz	50
GPSC5015	580x580x285	590x590	600x600	1500	DC5-12V trigger control / dry contact / remote	24	480x480x230	~220/50Hz	50
GPSC5010B	580x580x250	600x600	630x630	1000	DC5-12V trigger control / dry contact / remote	27	440x480x160	~220/50Hz	50
GPSC5015B	580x580x320	600x600	630x630	1500	DC5-12V trigger control / dry contact / remote	31	440x480x230	~220/50Hz	50