



### Features

- Aluminium bezel 80mm thick with Black flocked (VELVET) surface
- Pre-measured mounting brackets easy to install brackets
- Multi point tensioning system to ensure even tension for perfectly flat surface
- ISF Certified Fabric for big cinema experience at home
- Matt white and Acoustically Transparent fabric available
- Custom sizes available for large screens

Product Code	Ratio	Diagonal (inch)	Viewing area (mm)		Frame height (mm)	Overall width L (mm)	Overall height A (mm)	Fabric	Gain	View angle	Black back	Colour restoration	Shipping Dimensions (mm)		
			W	H									Width	Height	Depth
GRFF092H	16:9	92	2037	1145	80	2197	1305	Matt White	1.0	160 deg	Yes	96%	2325	270	175
GRFF095H	16:9	95	2103	1182	80	2263	1342	Matt White	1.0	160 deg	Yes	96%	2391	270	175
GRFF100H	16:9	100	2214	1245	80	2374	1405	Matt White	1.0	160 deg	Yes	96%	2502	270	175
GRFF105H	16:9	105	2324	1307	80	2484	1467	Matt White	1.0	160 deg	Yes	96%	2612	270	175
GRFF110H	16:9	110	2435	1369	80	2595	1529	Matt White	1.0	160 deg	Yes	96%	2725	270	175
GRFF115H	16:9	115	2546	1431	80	2706	1591	Matt White	1.0	160 deg	Yes	96%	2834	270	175
GRFF120H	16:9	120	2656	1494	80	2816	1654	Matt White	1.0	160 deg	Yes	96%	2944	270	175
GRFF130H	16:9	130	2877	1618	80	3037	1778	Matt White	1.0	160 deg	Yes	96%	3165	270	175
GRFF140H	16:9	140	3099	1742	80	3259	1902	Matt White	1.0	160 deg	Yes	96%	3387	270	175
GRFF150H	16:9	150	3320	1868	80	3480	2028	Matt White	1.0	160 deg	Yes	96%	3610	270	175
GRFF092H-AT	16:9	92	2037	1145	80	2197	1305	Accoustic Woven	0.8	150 deg	No	98%	2325	270	175
GRFF095H-AT	16:9	95	2103	1182	80	2263	1342	Accoustic Woven	0.8	150 deg	No	98%	2391	270	175
GRFF100H-AT	16:9	100	2214	1245	80	2374	1405	Accoustic Woven	0.8	150 deg	No	98%	2502	270	175
GRFF105H-AT	16:9	105	2324	1307	80	2484	1467	Accoustic Woven	0.8	150 deg	No	98%	2612	270	175
GRFF110H-AT	16:9	110	2435	1369	80	2595	1529	Accoustic Woven	0.8	150 deg	No	98%	2725	270	175
GRFF115H-AT	16:9	115	2546	1431	80	2706	1591	Accoustic Woven	0.8	150 deg	No	98%	2834	270	175
GRFF120H-AT	16:9	120	2656	1494	80	2816	1654	Accoustic Woven	0.8	150 deg	No	98%	2944	270	175
GRFF130H-AT	16:9	130	2877	1618	80	3037	1778	Accoustic Woven	0.8	150 deg	No	98%	3165	270	175
GRFF140H-AT	16:9	140	3099	1742	80	3259	1902	Accoustic Woven	0.8	150 deg	No	98%	3387	270	175
GRFF150H-AT	16:9	150	3320	1868	80	3480	2028	Accoustic Woven	0.8	150 deg	No	98%	3610	270	175
GRFF120CS-AT	2.35:1	120	2804	1193	80	2964	1353	Accoustic Woven	0.8	150 deg	No	98%	3092	270	175
GRFF130CS-AT	2.35:1	130	3038	1293	80	3198	1453	Accoustic Woven	0.8	150 deg	No	98%	3326	270	175
GRFF140CS-AT	2.35:1	140	3272	1392	80	3432	1552	Accoustic Woven	0.8	150 deg	No	98%	3560	270	175
GRFF150CS-AT	2.35:1	150	3505	1492	80	3665	1652	Accoustic Woven	0.8	150 deg	No	98%	3793	270	175

+ / - 10mm tolerance