

## ZW350e

Ultracompact high brightness laser projector



- **Bright WXGA DuraCore laser projector - 4000 lumens**
- **Small form factor for easy installation - 1.1x zoom, 360-degree and portrait projection**
- **DuraCore laser technology - 30,000 hours maintenance-free laser light source**
- **Built with the environment in mind - Long laser life span**



The ZW350e is Optoma's most compact hassle free WXGA DuraCore laser projector to date. Designed for maintenance-free continuous operation, it can be installed in virtually any orientation and location due to the small and lightweight footprint.

Designed with the environment in mind the ZW350e cuts power by 47% vs a typical Optoma lamp based product. Optoma have looked to minimize product design to cut logistic impacts on the environment cutting CO2 and reducing our overall carbon footprint.

## Specifications

<b>Display/image</b>	
Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness	4,000 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - vertical	+/-40°
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 140Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	0.76m ~ 7.62m (30" ~ 300") diagonal

<b>Lamp info</b>	
Light source type	Laser
LASER life	30,000 hours

<b>Optical</b>	
Throw ratio	1.54:1 ~ 1.72:1
Projection distance	1m - 10m
Zoom	1.1
Zoom type	Manual
Focal length	21.85 ~ 24.00
Native offset	112%

<b>Connectivity</b>	
Connections	<b>Inputs</b> 2 x HDMI 1.4a 3D support <b>Outputs</b> 1 x Audio 3.5mm, 1 x USB-A power 1.5A <b>Control</b> 1 x RS232

<b>General</b>	
Noise level (typical)	27dB
PC compatibility	WUXGA,1080P,UXGA, SXGA+,SXGA .WXGA+,WXGA,720P,XGA,SVGA,VGA
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Speaker count	1
Watts per speaker	15W
In the box	Power adaptor Remote control Basic user manual

<b>Power</b>	
Power supply	100V ~ 240V, 50-60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	89W
Power consumption (max)	140W

<b>Weight and dimensions</b>	
Dimensions (W x D x H)	274 x 216 x 114
Gross weight	4.2 kg
Net weight	3 kg

